

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number  
**WO 2005/009677 A1**

(51) International Patent Classification<sup>7</sup>: **B23Q 3/155,**  
3/157, B23B 31/26

[KR/KR]; 910-208 Jukong Apartment, Kojan 2-dong,  
Ansan-si, Kyungki-do 425-726 (KR).

(21) International Application Number:  
PCT/KR2004/000293

(74) Agent: **KIM, Kook Nam;** 2nd Fl. Shindo Building,  
823-10, Yeoksam-dong, Kangnam-ku, Seoul 135-080  
(KR).

(22) International Filing Date: 13 February 2004 (13.02.2004)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:  
10-2003-0051881 28 July 2003 (28.07.2003) KR


(71) Applicant (for all designated States except US): **YIWON  
ENGINEERING INC.** [KR/KR]; 2 Na 201, Sihwag-  
ongdan, 1260 Jungwang-dong, Siheung-si, Kyungki-do  
429-450 (KR).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,  
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

[Continued on next page]

(54) Title: APPARATUS FOR DETECTING POSITION OF DRAWBAR IN AUTOMATIC TOOL CHANGE DEVICE



(57) Abstract: Disclosed is an apparatus for de-  
tecting a position of a drawbar unit installed in a  
spindle unit. The apparatus is a part of an auto-  
matic tool exchange device for exchanging tools in  
the spindle unit of a machine tool. The apparatus  
transmits a signal to a main controller after detect-  
ing the position of the drawbar such that the main  
controller checks a state of a tool clamped by the  
drawbar unit. The drawbar unit is installed in the  
spindle unit forming the automatic tool exchange  
device and clamps the tool at a front thereof. A  
core is installed at a rear peripheral portion of the  
drawbar unit and a coil section having a cylindrical  
shape is wound around an outer peripheral portion  
of the core. An LC oscillating circuit is provided  
such that the LC oscillating circuit includes the coil  
section as a part thereof. An oscillating frequency  
of the LC oscillating circuit varies depending on  
a position of the core made of magnetic material,  
so the apparatus detects the position of the draw-  
bar unit based on the oscillating frequency of the  
LC oscillating circuit. A position detecting section  
transmits present position information of the draw-  
bar unit to a main controller, so the main controller  
detects the present position of the drawbar unit.



GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*